


Technical Data Sheet

Rosenberger

CABLE ASSEMBLY
SMP FEMALE / SMP FEMALE

L71-C1516-XXX



All dimensions are in mm; tolerances according to ISO 2768 c

Parts

Connector 1	SMP female	19K107-271L5
Connector 2	SMP female	19K107-271L5
Cable	RTK-FS 085-FEP (blue) (or equivalent type)	
Tube	Shrinking tube	
Label	Label Stick	

Available Variants Weight

Part Number	Customer Number	Length A[mm]	C[mm]	Insertion Loss ≤(dB) at 18GHz	Weight [Gram]
L71-C1516-1000	NA	1000±10	200±10	4.2	18.6

Electrical data

Impedance	50 Ω
Frequency	DC-18GHz
VSWR	≤1.5 to DC-18GHz
Insertion loss	see table available variants
Delay Matched	±2ps @10GHz (2pcs in one group)

Mechanical data

Minimum bending radius	6.0mm
Cable Diameter	2.6mm

Environmental data

Temperature range	-40°C to 85°C
RoHS	compliant

Draft	Date	Checker	Approved	Date	Rev.	Engineering change number	Name	Date
Liufei	04/08/17	Liujinghong	Liufei	04/08/17	a	NA	Liufei	04/08/17

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260
Tel. : +49 8684 18-0 Fax : +49 8684 18-499
www.rosenberger.de Email : info@rosenberger.de

D-84526 Tittmoning Germany

Page

1 / 1